

SPECIALTY OPTICAL FIBER

IXF-PMF-1950-125-P-021

Polarization-Maintaining Fiber

Exail proposes a range of standard PM Fibers with 125 μm cladding diameter.

Customized coatings and wavelengths available upon request.



Benefits & Features

- High birefringence
- Excellent polarization maintaining properties
- Low attenuation
- Dual-layer UV acrylate and 900 μm

Applications

- Coherent beam delivery
- Delay lines
- Diode & modulators pigtailed
- Fiber optic sensors, gyroscopes and instrumentation
- Lyot depolarizers
- Polarization-sensitive components

Parameters

Cutoff wavelength (nm)	1720 \pm 80
Attenuation @1950nm (dB/km)	< 11.5
Attenuation @2000nm (dB/km)	< 22.5
Beat length @1950nm (mm)	< 5.2
Mode field diameter @1950nm (μm)	8 \pm 1
Numerical aperture	0.21 \pm 0.01
Core/Clad concentricity (μm)	< 1
Cladding diameter (μm)	125 \pm 1
Coating diameter (μm)	250 \pm 15
Proof test level (kpsi)	100

Design parameters

Operating wavelength (nm)	1850 - 2200
Design	Panda
Holding parameter @1550nm (m^{-1})	< 1.10^{-5}
Coating material	Dual acrylate
Operating temperature range ($^{\circ}\text{C}$)	-40 to +85

Exail reserves the right to change, at any time and without notice, the specifications, design, function or form of its products described herein.

contact.photonics@exail.com | www.exail.com
Europe +33 1 30 08 94 50 | Americas +1 508 745 3487 | APAC +60 11 1623 1698

exail