

SPECIALTY OPTICAL FIBER

IXF-PMF-740-125-P-021

Polarization-Maintaining Fiber

Exail proposes a range of standard PM Fibers with 125 μm cladding diameter.

Customized coatings and wavelengths available upon request.



Benefits & Features

- High birefringence
- Excellent polarization maintaining properties
- Low attenuation
- Dual-layer UV acrylate and 900 μm

Applications

- Coherent beam delivery
- Delay lines
- Diode & modulators pigtailed
- Fiber optic sensors, gyroscopes and instrumentation
- Lyot depolarizers
- Polarization-sensitive components

Parameters

Cutoff wavelength (nm)	600 \pm 50
Attenuation @700nm (dB/km)	< 12
Beat length @740nm (mm)	< 1.8
Mode field diameter @780nm (μm)	3 \pm 0.5
Numerical aperture	0.21 \pm 0.01
Core/Clad concentricity (μm)	< 0.5
Cladding diameter (μm)	125 \pm 1
Coating diameter (μm)	245 \pm 15
Proof test level (kpsi)	100

Design parameters

Operating wavelength (nm)	700 - 850
Design	Panda
Core shape	Round
Operating temperature range ($^{\circ}\text{C}$)	-40 to +85

Exail reserves the right to change, at any time and without notice, the specifications, design, function or form of its products described herein.

contact.photonics@exail.com | www.exail.com
Europe +33 1 30 08 94 50 | Americas +1 508 745 3487 | APAC +60 11 1623 1698

exail