

SPECIALTY OPTICAL FIBER

IXF-PZG-1310-80

Polarizing Fiber

Exail Polarizing (PZ) fiber is designed so that only one state of polarization is guided along the fiber; any other state of polarization will be lost rapidly thus yielding a high built-in polarization extinction ratio. This particular mechanism is obtained through a specific waveguide design and a careful optimization of the glass composition resulting in both high birefringence and leakage behavior.

PZ fibers are available at different wavelengths with a broad polarizing window (typically larger than 100 nm), low attenuation and high extinction ratio (≥ 30 dB), that can be tuned by coiling the proper fiber length at the appropriate coil diameter.

If needed Exail also offers ready to use polarizing solutions based on PZ fibers.



Benefits & Features

- All-fiber polarizer
- Coiled operation
- Polarizing wavelengths available: 780, 840, 980, 1060, 1310 or 1550 nm
- Fiber diameter: 80 or 125 μm
- Tiger design
- > 100 nm polarizing window
- > 30 dB extinction ratio

Applications

- Quantum optics, cold atoms
- All-Fiber polarizer
- Fiber optic current sensors and gyros

Parameters

20 dB fast edge* (nm)	< 1270
3 dB slow edge* (nm)	> 1370
Extinction ratio (dB)	< -30
Attenuation @1310nm (dB/km)	< 20
Mode field diameter @1310nm (μm)	9 ± 2.5
Numerical aperture	0.13 ± 0.01
Core/Clad concentricity (μm)	< 1
Cladding diameter (μm)	80 ± 2
Coating diameter (μm)	170 ± 5
Proof test level (kpsi)	100

Design parameters

Operating wavelength (nm)	1310
Design	Tiger
Core shape	Round
Coating material	Dual acrylate
Operating temperature range ($^{\circ}\text{C}$)	-40 to $+85$

Comments:

**Typical polarization performance with deployment conditions of 5m length in a 80mm coil.*

Exail reserves the right to change, at any time and without notice, the specifications, design, function or form of its products described herein.

contact.photonics@exail.com | www.exail.com
Europe +33 1 30 08 94 50 | Americas +1 508 745 3487 | APAC +60 11 1623 1698

exail