


## SPACE GRADE MODULATOR

# EM/NS-FM/FM/-MXER-LN-10

## C-band 10 GHz Space Grade High Extinction Ratio Modulator

The MXER-LN-10 is an electro-optical amplitude modulator featuring a very high extinction ratio and a very wide bandwidth above 10 GHz. Its specific design relies on Exail "Magic Junction" (patent n° US2008193077) to achieve a very low insertion loss and high extinction ratio values.

The MXER-LN-10 is ready for space, and several Space Grades modulator versions are proposed. An EM-/NS-FM-/FM-/MXER-LN-10 modulator version can be purchased to match the user application and space mission requirements.



### MXER-LN-10 Performance Highlights

#### Features

- Optical power up to 20 dBm
- High extinction ratio
- Low insertion losses
- Low  $V_{\pi}$

#### Applications

- High pulse contrast
- Pulse-position modulation (PPM)
- Quantum Key Distribution (QKD)
- Lidar

#### Related Equipments

- MPZ C-Band phase modulators

Parameter	Min	Typ	Max	Unit
Operating wavelength	1535	1550	1560	nm
Usable EO bandwidth	-	12	-	GHz
$V_{\pi}$ RF @50 kHz	-	5.5	6	V
Insertion loss (without connector)	-	4	5	dB
RF port input impedance	-	50	-	$\Omega$

### Space Grade Modulator Versions and Definition <sup>(1)</sup>

Modulator grade		Terrestrial Grade TG <sup>(2)</sup>	Engineering Model EM	New-Space Flight Model NS-FM	Flight Model FM
	Flight compatibility	X	X	O	O
Assembly	Space compatible raw material	X	O	O	O
	Batch unicity	X	X	X	O
	Space compatible assembly process	X	X	O	O
Test	Screening test	Partial	Partial	O	O
	Space qualification test	X	X	O	O
	Lot acceptance test	X	X	X	O
	Qualification program	X	X	X	O
Documentation	Acceptance test report	O	O	X	X
	Interface control document	X	O	O	O
	Certificate of conformity	X	O	O	O
	Screening test report	X	X	O	O
	Lot acceptance test report	X	X	X	O
	Handling manual	O	O	O	O

<sup>(1)</sup> O: apply. X: do not apply

<sup>(2)</sup> Please refer to the MXER Series commercial data-sheet, <https://www.ixblue.com/wp-content/uploads/2022/01/MXER-LN%20SERIES.pdf>.

## SPACE GRADE MODULATORS

# EM-MXER-LN-10

## Space Grade High Extinction Ratio Modulator - Engineering Model

The engineering model is flight representative in form, fit and function. The engineering models are used for functional qualification, except redundancy verification, failure survival demonstration and parameter drift checking. The EM is also used for final validation of test facilities. (ECSS-E-10-02A).

### Electrical Characteristics

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Electro-optical (EO) bandwidth	$S_{21}$	-	10	12	-	GHz
Ripple $S_{21}$	$\Delta S_{21}$	RF electrodes, $f < 10$ GHz	-	0.5	1	dB
Electrical return loss	$S_{11}$	RF electrodes, $f < 10$ GHz	-	-12	-10	dB
$V\pi$ RF @50 kHz	$V\pi_{RF\ 50\ kHz}$	RF electrodes	-	5.5	6	V
$V\pi$ DC	$V\pi_{DC}$	DC electrodes	-	6.5	7	V
RF port input impedance	$Z_{in-RF}$	-	-	50	-	$\Omega$
DC port input impedance	$Z_{in-DC}$	-	1	-	-	M $\Omega$

### Optical Characteristics

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Crystal	-	-	Lithium Niobate X-Cut Y-Prop			
Operating wavelength	$\lambda$	-	1535	1550	1560	nm
Insertion loss	IL	Without connector <sup>(1)</sup>	-	4	5	dB
DC static extinction ratio	SER	Note <sup>(2)</sup>	30	35	-	dB
Polarization extinction ratio	PER	Without connector	20	-	-	dB
Optical return loss	ORL	-	-40	-	-	dB
Chirp	-	-	-0.1	-	+0.1	-

<sup>(1)</sup> Consider an extra-loss up to 0.4 dB for each FC/APC commercial grade optical connector, and up to 0.5 dB for each Mini-Avim® and Avim® optical connector.

<sup>(2)</sup> Measured with narrow source, linewidth  $\leq 200$  MHz.

### Absolute Maximum Ratings

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of the data sheet. Exposure to absolute maximum ratings for extended periods can adversely affect device reliability.

Parameter	Symbol	Min	Max	Unit
Maximum RF input power (CW mode)	$RF_{in}$	-	+28	dBm
Bias voltage	$DC_{in}$	-20	+20	V
Optical input power (CW mode)	$OP_{in}$	-	+20	dBm
Operating temperature (no applied derating)	OT	+0	+70	$^{\circ}C$
Storage temperature	ST	-40	+85	$^{\circ}C$

## SPACE GRADE MODULATORS

# EM-MXER-LN-10

## Space Grade High Extinction Ratio Modulator - Engineering Model

### Interfaces and dimensions

Input fiber	Polarization maintaining 1550 nm - Corning PM 15-U25D - Length: typ. 1.5 meter
Output fiber	Polarization maintaining 1550 nm - Corning PM 15-U25D - Length: typ. 1.5 meter
Fibers jacket	1 mm PEEK loose tube
Input RF connector	Female K
Optical connectors (optional)	No connector Commercial grade FC/APC
Optical connectors orientation	Slow axis parallel to the connector key
Package size	110 x 15 x 9.7 mm <sup>3</sup>
Mass	46 g
Package Lid	Laser marked
Materials	Low outgassing

### Screening <sup>(1)</sup>

Test	Conditions
Thermal cycling	EOM non-operational -40 °C / +85 °C
Final tests after screening	Room temperature

<sup>(1)</sup>Please refer to «00025954-A - MX & MXER Space Model - Screening Test and LAT.pdf» documentation.

### Documentation

Acceptance Test Report

Interface Control Document

Certificate of Conformity

Handling Manual

## SPACE GRADE MODULATORS

# NS-FM-MXER-LN-10

## Space Grade High Extinction Ratio Modulator - New-Space Flight Model

The New Space Flight Model (NS-FM) are the modulators dedicated to fly, based on qualification heritage (available on demand). The New-Space Flight Model are modulators that are used for the confirmation of key performances and interface, including unit mounting scheme and thermal characteristics. These modulators are identical to flight hardware, it is sampled from flight model lot after screening test. Those modulators are not evaluated with a Lot Acceptance Test.

### Electrical Characteristics

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Electro-optical (EO) bandwidth	$S_{21}$	-	10	12	-	GHz
Ripple $S_{21}$	$\Delta S_{21}$	RF electrodes, $f < 10$ GHz	-	0.5	1	dB
Electrical return loss	$S_{11}$	RF electrodes, $f < 10$ GHz	-	-12	-10	dB
$V\pi$ RF @50 kHz	$V\pi_{RF\ 50\ kHz}$	RF electrodes	-	5.5	6	V
$V\pi$ DC	$V\pi_{DC}$	DC electrodes	-	6.5	7	V
RF port input impedance	$Z_{in-RF}$	-	-	50	-	$\Omega$
DC port input impedance	$Z_{in-DC}$	-	1	-	-	M $\Omega$

### Optical Characteristics

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Crystal	-	-	Lithium Niobate X-Cut Y-Prop			
Operating wavelength	$\lambda$	-	1535	1550	1560	nm
Insertion loss	IL	Without connector <sup>(1)</sup>	-	4	5	dB
DC static extinction ratio	SER	Note <sup>(2), (3)</sup>	30	35	-	dB
Polarization extinction ratio	PER	Without connector	20	-	-	dB
Optical return loss	ORL	-	-40	-	-	dB
Chirp	-	-	-0.1	-	+0.1	-

<sup>(1)</sup> Consider an extra-loss up to 0.4 dB for each FC/APC commercial grade optical connector, and up to 0.5 dB for each Mini-Avim® and Avim® optical connector.

<sup>(2)</sup> Measured with narrow source, linewidth  $\leq 200$  MHz.

<sup>(3)</sup> The modulator's ER is warranted in the range [0 °C, +70 °C]. Qualification has not been performed for the full operating temperature range [-30 °C, +70 °C].

### Absolute Maximum Ratings

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of the data sheet. Exposure to absolute maximum ratings for extended periods can adversely affect device reliability.

Parameter	Symbol	Min	Max	Unit
Maximum RF input power (CW mode)	$RF_{in}$	-	+28	dBm
Bias voltage	$DC_{in}$	-20	+20	V
Optical input power (CW mode)	$OP_{in}$	-	+20	dBm
Operating temperature (no applied derating)	OT	-30	+70	°C
Storage temperature	ST	-40	+85	°C

## SPACE GRADE MODULATORS

# NS-FM-MXER-LN-10

## Space Grade High Extinction Ratio Modulator - New-Space Flight Model

### Interfaces and dimensions

Input fiber	Polarization maintaining 1550 nm - Corning PM 15-U25D - Length: typ. 1.5 meter
Output fiber	Polarization maintaining 1550 nm - Corning PM 15-U25D - Length: typ. 1.5 meter
Fibers jacket	1 mm PEEK loose tube
Input RF connector	Female K
Optical connectors (optional)	No connector Commercial grade FC/APC Space grade Mini-Avim® / Avim®
Optical connectors orientation	Slow axis parallel to the connector key
Package size	110 x 15 x 9.7 mm <sup>3</sup>
Mass	46 g
Package Lid	Laser marked
Materials	Low outgassing

### Screening <sup>(1)</sup>

Test	Conditions
Initial tests before screening	Room temperature
Thermal cycling	EOM non operational -40 °C / +85 °C
Burn-in	EOM operational +70 °C
Thermal cycling	EOM operational -30 °C / +70°C
Final tests after screening	Room temperature

<sup>(1)</sup>Please refer to «00025954-A - MX & MXER Space Model - Screening Test and LAT.pdf» documentation.

### Qualification legacy

Sub-group	Test	Conditions
Mechanical	Sine vibrations	20 g
	Random vibrations	33.6 grms
	Shocks	1600 g
Radiations	Total Ion Dose	360 krad
	Total Non Ionizing Dose	E = 60 MeV, $\phi = 6 \times 10^{11}$ p+/cm <sup>2</sup>
Thermal cycling	Ambient pressure	-40 °C / +85 °C, 500 cycles non-operational
	Vacuum	-30 °C / +70 °C, 20 cycles non-operational
Lifetest	Ageing	+85 °C, 1000 h
Moisture	Damp heat	+85 °C, 85 % RH, 240 h

### Documentation

Interface Control Document - Certificate of Conformity

Screening test report - Handling Manual

Other documents available on request (Test plan, DML, DPL, DCL, ABCL, MFC...)

## SPACE GRADE MODULATORS

# FM-MXER-LN-10

## Space Grade High Extinction Ratio Modulator - Flight Model

The Flight Model (FM) are the modulators dedicated to fly; these are tested to acceptance-level testing (LAT Lot Acceptance Tests corresponding to a relaxed qualification tests program). (ECSS-E-10-02A).

### Electrical Characteristics

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Electro-optical (EO) bandwidth	$S_{21}$	-	10	12	-	GHz
Ripple $S_{21}$	$\Delta S_{21}$	RF electrodes, $f < 10$ GHz	-	0.5	1	dB
Electrical return loss	$S_{11}$	RF electrodes, $f < 10$ GHz	-	-12	-10	dB
$V\pi$ RF @50 kHz	$V\pi_{RF\ 50\ kHz}$	RF electrodes	-	5.5	6	V
$V\pi$ DC	$V\pi_{DC}$	DC electrodes	-	6.5	7	V
RF port input impedance	$Z_{in-RF}$	-	-	50	-	$\Omega$
DC port input impedance	$Z_{in-DC}$	-	1	-	-	M $\Omega$

### Optical Characteristics

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Crystal	-	-	Lithium Niobate X-Cut Y-Prop			
Operating wavelength	$\lambda$	-	1535	1550	1560	nm
Insertion loss	IL	Without connector <sup>(1)</sup>	-	4	5	dB
DC static extinction ratio	SER	Note <sup>(2), (3)</sup>	30	35	-	dB
Polarization extinction ratio	PER	Without connector	20	-	-	dB
Optical return loss	ORL	-	-40	-	-	dB
Chirp	-	-	-0.1	-	+0.1	-

<sup>(1)</sup> Consider an extra-loss up to 0.4 dB for each FC/APC commercial grade optical connector, and up to 0.5 dB for each Mini-Avim® and Avim® optical connector.

<sup>(2)</sup> Measured with narrow source, linewidth  $\leq 200$  MHz.

<sup>(3)</sup> The modulator's ER is warranted in the range [0 °C, +70 °C]. Qualification has not been performed for the full operating temperature range [-30 °C, +70 °C].

### Absolute Maximum Ratings

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of the data sheet. Exposure to absolute maximum ratings for extended periods can adversely affect device reliability.

Parameter	Symbol	Min	Max	Unit
Maximum RF input power (CW mode)	$RF_{in}$	-	+28	dBm
Bias voltage	$DC_{in}$	-20	+20	V
Optical input power (CW mode)	$OP_{in}$	-	+20	dBm
Operating temperature (no applied derating)	OT	-30	+70	°C
Storage temperature	ST	-40	+85	°C

## SPACE GRADE MODULATORS

# FM-MXER-LN-10

## Space Grade High Extinction Ratio Modulator - Flight Model

### Interfaces and dimensions

Input fiber	Polarization maintaining 1550 nm - Corning PM 15-U25D - Length: typ. 1.5 meter
Output fiber	Polarization maintaining 1550 nm - Corning PM 15-U25D - Length: typ. 1.5 meter
Fibers jacket	1 mm PEEK loose tube
Input RF connector	Female K
Optical connectors (optional)	No connector Commercial grade FC/APC Space grade Mini-Avim® / Avim®
Optical connectors orientation	Slow axis parallel to the connector key
Package size	110 x 15 x 9.7 mm <sup>3</sup>
Mass	46 g
Package Lid	Laser marked
Materials	Low outgassing

### Screening <sup>(1)</sup>

Test	Conditions
Initial tests before screening	Room temperature
Thermal cycling	EOM non operational -40 °C / +85 °C
Burn-in	EOM operational +70 °C
Thermal cycling	EOM operational -30 °C / +70 °C
Final tests after screening	Room temperature

<sup>(1)</sup> Please refer to «00025954-A - MX & MXER Space Model - Screening Test and LAT.pdf» documentation.

### Qualification legacy

Sub-group	Test	Conditions
Mechanical	Sine vibrations	20 g
	Random vibrations	33.6 grms
	Shocks	1600 g
Radiations	Total Ion Dose	360 krad
	Total Non Ionizing Dose	E = 60 MeV, $\phi = 6 \times 10^{11}$ p+/cm <sup>2</sup>
Thermal cycling	Ambient pressure	-40 °C / +85 °C, 500 cycles non-operational
	Vacuum	-30 °C / +70 °C, 20 cycles non-operational
Lifetest	Ageing	+85 °C, 1000 h
Moisture	Damp heat	+85 °C, 85 % RH, 240 h

## SPACE GRADE MODULATORS

# FM-MXER-LN-10

## Space Grade High Extinction Ratio Modulator - Flight Model

### Flight Model Lot Acceptance Test (LAT) <sup>(1)</sup>

Proposition of Lot Acceptance Test sequence - on request modification available

Sub-group	Test	Conditions
Mechanical	Vibration test	25 grms 1 min/axis - 1 axis (out of plane)
Thermal cycling	Non-operating temperature test	EOM non operational [-35 °C ; +60 °C]
	Operating temperature test	EOM operational [+10 °C; +20 °C; +55 °C]

<sup>(1)</sup> Please refer to «00025954-A - MX & MXER Space Model - Screening Test and LAT.pdf» documentation.

### Documentation

Interface Control Document

Certificate of Conformity

Screening & LAT test report

Handling Manual


Other documents available on request (Test plan, DML, DPL, DCL, ABCL, MFC...)



# SPACE GRADE MODULATORS

## Mechanical Diagram and Pinout

All measurements in mm



EM / NS-FM / FM

Input connector: 00 (bare fiber), FA (FC/APC),

AV (space grade AVIM®), MAV (space grade Mini-AVIM®) (for NS-FM and FM only)

Output connector: 00 (bare fiber), FA (FC/APC),

AV (space grade AVIM®), MAV (space grade Mini-AVIM®) (for NS-FM and FM only)

□ -MXER-LN-10-00-P-P - □ - □

### About us

Exail Photonics produces specialty optical fibers and Bragg gratings based fiber optics components and provides optical modulation solutions based on the company lithium niobate (LiNbO<sub>3</sub>) modulators and RF electronic modules.

Exail Photonics serves a wide range of industries: sensing and instruments, defense, telecommunications, space and fiber lasers as well as research laboratories all over the world.

Exail reserves the right to change, at any time and without notice, the specifications, design, function or form of its products described herein. All statements, specification, technical information related to the products herein are given in good faith and based upon information believed to be reliable and accurate at the moment of printing. However, Exail provides no warranty (whether express or implied or statutory) as to the description, sufficiency, accuracy or completeness, merchantability or fitness for a particular purpose of any information or specification detailed herein. No liability is assumed for any inaccuracies and/or as a result of use of the products. The user must validate all parameters for each application before any use and he shall assume all risks and responsibilities in connection with the use of the products.