

SPECIALTY OPTICAL FIBER


IXF-SM-1550-125-014-AL

Single Mode Fiber

The IXF-SM family includes singlemode fibers designed for use in harsh environments with extreme temperatures and/or low to moderate radiation levels. Exail offers a wide range of polymer and metallic coatings well-suited for high-temperature applications.

Aluminum coated fibers offer a wide operating temperature range, from cryogenic temperatures up to +400 °C. They are also hermetic to hydrogen, mitigating hydrogen darkening in hydrogen-rich environments.

The IXF-SM-1550-125-014-AL fiber is radiation tolerant and can be used under low to moderate radiation levels, a matching radiation hardened fiber is available for high radiation levels.



Benefits & Features

- Singlemode operation at 1310 and 1550 nm
- Aluminum coating
- Operating temperature up to +400 °C
- Radiation tolerant for low to moderate radiation levels
- Matching radiation hardened fiber available
- Hermetic to hydrogen and water vapor
- Solderable directly to connectors
- Low splice loss to SMF28

Applications

- Transport fiber
- Sensing
- Distributed Temperature Sensing (DTS)

Related Products

- | | |
|---------------------------|---------------------|
| • IXF-RAD-SM-1550-014-AL | Rad-Hard fiber |
| • IXF-SM-1550-125-019-AL | NA 0.19 |
| • IXF-SM-1550-125-0.14-PI | Polyimide coating |
| • IXF-SM-1550-125-0.14-HT | HT acrylate coating |

Parameters

Cutoff wavelength (nm)	$1150 \leq \lambda_c \leq 1275$
Attenuation @1310 nm (dB/km)	≤ 20
Attenuation @1550 nm (dB/km)	≤ 20
Mode field diameter @1310 nm (μm)	7.8 ± 0.5
Mode field diameter @1550 nm (μm)	9 ± 0.5
Numerical aperture	0.14 ± 0.01
Core/Clad concentricity (μm)	≤ 1
Cladding diameter (μm)	125 ± 2
Coating diameter (μm)	170 ± 10
Proof test level (kpsi)	100

Design parameters

Operating wavelength (nm)	1300 - 1650
Coating material	Aluminum
Operating temperature range (°C)	-269 to +400
Short term bend radius (mm)	15
Long term bend radius (mm)	30



[More information about the 3F2E project](#)

Exail reserves the right to change, at any time and without notice, the specifications, design, function or form of its products described herein.

contact.photonics@exail.com | www.exail.com
Europe +33 1 30 08 94 50 | Americas +1 508 745 3487 | APAC +60 11 1623 1698

exail